



Rentals • Sales • Service
24/7 • (800) 227-1966

1.2M Grain Triple Alternating Mobile Softener Room

Nationwide Boiler's 1.2M grain triple alternating mobile water softener room, 30-100 psig operating pressure, is fully piped and wired. It includes the following components:

- Triplex Marlo Water Softener System
- Brine Tank
- Alternating Stage Controller
- Softener Control Valve
- Raw Water Supply Shutoff Valve
- Softener Supply Sample Valve
- Softener Tank Supply Shutoff Valve
- Inline Flow Meter



Rated Flow:

Minimum: 61 GPM
 Maximum: 180 GPM

Backwash Flow:

Minimum: 30 GPM
 Maximum: 60 GPM

Total Flow:

Minimum: 96 GPM
 Maximum: 250 GPM

Pressure Drop:

Normal Flow: 15 psig
 Peak Flow: 25 psig

Maximum Pressure: 100 psig

Minimum Pressure: 30 psig

Brine Tank Capacity: 1,760 lbs. salt

Connection Sizes:

Raw Water Inlet: 3"-150# RF FLG

Softwater Outlet: 3"-150# RF FLG

Drain Outlet: 1 1/2" NPT

Bypass Valve (normally closed): 3" NPT

Electrical Power Requirements:

Control: 120 VAC, 60 Hz, 15 Amps High: 460 VAC, 60 Hz, 36 Amps

Dimensions & Weights:

Height: 13' 4"

Width: 8'

Length: 23' 8"

Shipping Weight Dry: 21,660 lbs. (less salt)

Operating Weight: 40,115 lbs.

Ask About Our **Green Solutions**

CataStakTM
 Ultra Low NOx Solutions

EconoStakTM
 Energy Saving Solutions

42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com

True Nationwide Coverage & Beyond. Representatives Located Worldwide.

* Actual Equipment may differ from listed specification. Please consult Nationwide Boiler Inc. for additional details.