

Rentals • Sales • Service

475 HP New In Stock Ultra Low NOx, 150 psig Skid-Mounted Boiler

Nationwide Boiler's ultra low NOx, 475 hp (16,388 lbs/hr) Superior Sierra skid-mounted boiler is designed at 150 psig firing natural gas. It is fully piped and wired and includes the following components:

- 475 hp Superior Sierra Firetube Boiler Package
- Webster Ultra Low NOx Burner
- Integral Economizer for 83% Minimum Efficiency
- 40 hp TEFC Blower Motor (w/ VFD shipped loose)
- . 3-Pass XI-D Tube Design
- 3" Main Gas Pressure Regulator (mounted)
- NEMA 4 Control Panel w/ Siemens LMV Parallel Positioning Controls
- O2 Trim
- Valve Trim (safeties, drain, etc.)
- Blowdown Valves (mounted & pre-piped) .
- 4" Non-return Valve & 2nd Steam Gate Valve (loose)
- 8" x 4" ASME Reducer Spool (loose)
- Single Point 480V Electrical Disconnect Connection w/ Step Down 115V Transformer
- Modulating Feedwater Control Valve w/ **3 Valve Bypass**
- Integral Seismic Anchor Plates
- Meets ASME Section I, Cal Code, CSD-1, **IRI and NFPA-85 Requirements**
- Weatherproofed (except for freezing conditions) for Indoor / Outdoor use
- Operating Manuals on CD's

*Pre-Tested for Proven Performance!



Fuel Consumption:

Natural Gas:

19,950 SCFH @ 5-10 psig regulated

Connection Sizes:	
Steam:	4-300# FLG
Natural Gas:	3" NPT
Blowdown/Drain:	1½" NPT
Surface Blowdown:	1" NPT
Feedwater:	2" NPT
Exhaust Stack:	24" Round

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 60 AMPS

Dimensions & Weights:

Emissions Data (natural gas):

NOx (corr. to 3% O₂): 5 ppm CO (corr. to 3% O₂): 50 ppm

Ask About Our Green Solutions

42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.

* Actual equipment may differ from listed specification. Please consult Nationwide Boiler Inc. for additional details.