



Rentals • Sales • Leasing
24/7 • (800) 227-1966

75,000 pph
Low NOx, 750 psig / 750°F
Trailer-Mounted Superheat Boiler

Nationwide Boiler's low NOx, 75,000 pph, 750 psig / 750°F design superheat, trailer-mounted package watertube Babcock & Wilcox boiler is set to burn natural gas (#2 oil is optional). It is fully piped and wired and includes the following components:

- Low NOx Burner
- EconoStak Economizer
- Burner Management System
- Parallel Positioning Combustion Controls
- Forced Draft Fan, Motor & Starter
- Complete Fuel Train & Pilot Ignition System
- Water Column & Site Glass
- Steam Pressure Gauge
- Low-water Cutoffs
- Safety Valves
- Feedwater Stop & Check Valves
- Blowdown Valves
- Continuous Blowdown Metering Valve
- Chemical Feed Valve
- Single Element Feedwater Regulator with Pre-piped 3-Valve Bypass
- Steam Non-return Valve (loose)
- Stack (loose)
- NEMA 4 Electrical Enclosures
- Seperate Fuel Oil Skid for #2 Oil Firing (optional)
- Low NOx CataStak™ SCR System (optional)
- Weatherproofed (except for freezing)
- Meets FM, NFPA 85 & IRI Insurance Standards
- Operating Manuals



Fuel Consumption:

Natural Gas: 99,000 SCFH
 #2 Oil (optional): 745 GPH

Connection Sizes:

Main Steam: 8"-600# FLG
 Natural Gas: 4"-150# FLG
 #2 Oil Supply: 1" NPT
 Feedwater: 2½"-600# FLG
 Bottom Blowdown: 1½"-600# FLG
 Continuous Blowdown: ¾" NPT
 Chemical Feed: ½" NPT
 Atomizing Steam: 1" NPT
 Instrument Air: ½" NPT
 Water Column Drain: ¾" NPT

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 200 AMPS

Boiler Dimensions & Weights:

Length* / Width / Height: 46' 10" / 10' 0" / 14' 0"
 Shipping Weight: 126,000 lbs
 Operating Weight*: 170,000 lbs

* less removable rear axle and gooseneck / weight includes economizer

Emissions Data (natural gas):

NOx (corr. to 3% O₂): 30 ppm
 CO (corr. to 3% O₂): 50 ppm

Ask About Our **Green Solutions**



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com

True Nationwide Coverage & Beyond. Representatives Located Worldwide.

* Actual Equipment may differ from listed specification. Please consult Nationwide Boiler Inc. for additional details.