



Rentals • Sales • Leasing
24/7 • (800) 227-1966

125 hp, 30 psig Hydronic Heating Skid-Mounted Boiler

Nationwide Boiler's 125 hp (4.18 mmbtu) skid-mounted Cleaver-Brooks hydronic heating firetube boiler is designed at 30 psig pressure, firing natural gas or #2 oil. It is fully piped and wired and includes the following components:

- 125 hp Cleaver-Brooks Hydronic Heating Boiler
- Burner
- Pilot Ignition System
- Honeywell RM7800 Flame Safeguard w/ Display Module
- Dual Low Water Cutoffs
- Pressure Gauge
- Safety Pressure Relief Valves
- Hot Water Supply & Return Isolation Valves (installed)
- Drain Valves (installed)
- Hot Water Supply Pump (7.5 hp, 190 gpm @ 60' TDH) with a 40°F Temperature Ride
- Fused Disconnect Switch
- #2 Fuel Oil Pump
- Forced Draft Fan, Motor & Starter
- Stack (loose)
- Meets FM / IRI Insurance
- Operating Manuals



Fuel Consumption:

Natural Gas: 5,100 SCFH @ 3-15 psig
 #2 Oil: 37.5 GPH @ 2 psig

Connection Sizes:

Hot Water Supply: 3"-150# FLG
 Hot Water Return: 6"-150# FLG
 Natural Gas: 3"-150# FLG
 #2 Oil Supply: ½" NPT
 #2 Oil Return: ½" NPT
 Drain: 1½" NPT

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 60 AMPS

Dimensions & Weights:

Length: 14' 11"
 Width (incl. HW pump): 8' 9"
 Height (floor to piping): 10' 0"
 Shipping Weight: 14,900 lbs
 Operating Weight: 23,030 lbs

Ask About Our **Green Solutions**

CataStakTM
 Ultra Low NOx Solutions

EconoStakTM
 Energy Saving Solutions

42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com

True Nationwide Coverage & Beyond. Representatives Located Worldwide.