



Rentals • Sales • Leasing
24/7 • (800) 227-1966

60,000 pph
Low NOx, 300 psig
Trailer-Mounted Boiler

Nationwide Boiler's low NOx, 300 psig saturated, 60,000 pph Trailer-Mounted package watertube Nebraska boiler is set to burn Natural Gas/#2 Oil. It includes the following:

- Site Glass
- Steam Pressure Gauge
- Low-water Cutoffs
- Water Column
- Safety Valves
- FW Stop & Check Valves
- Blowdown Valves
- Continuous Blowdown Metering Valve
- Chemical Feed Valve
- Single Element Pneumatic FW Regulator
- Low NOx Burner
- Burner Management System
- Pilot Ignition System
- Forced-draft Fan, Motor & Starter
- Single-point Positioning Combustion Controls
- Control Circuit Step Down Transformer for 120 volt Supply
- Fused Electrical Disconnect
- No. 2 Fuel Oil Pump
- Economizer Piping Mounted on Unit
- Steam Non-return Valve
- Stub Stack
- NEMA 4 Electrical Enclosures
- Meets FM / IRI Insurance
- Meets NFPA 85
- Weatherproofed



Connection Sizes:

Main Steam:	8"-300# FLG.
Oil:	1 1/2" NPT supply, 3/4" NPT return
Gas:	3"-150# FLG.
Feedwater:	2 1/2"-300# FLG.
Bottom Blowdown:	1 1/2"-300 # FLG.
Continuous Blowdown:	1" NPT
Chemical Feed:	1" NPT
Atomizing Air / Steam:	1" NPT 80 scfm @ 125 psig / 1 1/4" NPT 800 pph @ 150 psig
Instrument Air:	1/4" NPT
Water Column Drain:	3/4" NPT

Electrical Power Requirements:

230/460 VAC, 3 ph, 60 Hz, 65 kw

Dimensions & Weights:

Length:	49' 5"
Width:	10' 0"
Height:	14' 0"
Boiler & Trailer:	83,800 lbs
Operating:	99,500 lbs

Ask About Our **Green Solutions**

