Nationwide™ Boiler Incorporated

Rentals • Sales • Leasing
24/7 • (800) 227-1966

125 hp, 30 psig Hydronic Heating Skid-Mounted Boiler

Nationwide Boiler's 125 hp (4.18 mmbtu) skid-mounted Cleaver-Brooks hydronic heating firetube boiler is designed at 30 psig pressure, firing natural gas or #2 oil. It is fully piped and wired and includes the following components:

- 125 hp Cleaver-Brooks Hydronic Heating Boiler
- Burner
- Pilot Ignition System
- Honeywell RM7800 Flame Safeguard w/ Display Module
- Dual Low Water Cutoffs
- Pressure Gauge
- Safety Pressure Relief Valves
- Hot Water Supply & Return Isolation Valves (installed)
- Drain Valves (installed)
- Hot Water Supply Pump (7.5 hp, 190 gpm @ 60' TDH)
- Fused Disconnect Switch
- #2 Fuel Oil Pump
- Forced Draft Fan, Motor & Starter
- Stack (loose)
- Meets FM / IRI Insurance
- Operating Manuals

Fuel Consumption:

Natural Gas:	5,100 SCFH @ 3-15 psig
#2 Oil:	37.5 GPH @ 2 psig

Connection Sizes:

Hot Water Supply:	3"-150# FLG
Hot Water Return:	6"-150# FLG
Natural Gas:	3"-150# FLG
#2 Oil Supply:	½" NPT
#2 Oil Return:	½" NPT
Drain:	1½" NPT

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 50 amp

Dimensions & Weights:

Length:	14' 11"
Width (incl. HW pump):	8' 9"
Height (floor to piping):	10' 0"
Shipping Weight:	14,900 lbs
Operating Weight:	23,030 lbs

Ask About Our **Green Solutions**

CataStak™ Ultra Low NOx Solutions

EconoStak Energy Saving Solutions

42400 Christy Street / Fremont, CA 94538 / (800) 227-1966 / www.nationwideboiler.com / info@nationwideboiler.com
San Francisco • Baton Rouge • Birmingham • Edmonton • Charlotte • Council Bluffs • Cleveland • Montreal • Houston • Philadelphia • Seattle • Venezuela

** Actual equipment may differ from listed specification. Please consult Nationwide Boiler Inc. for additional details.*