

Rentals • Sales • Service

119 HP Ultra Low NOx, 200 psig Skid-Mounted **Boiler System**

Nationwide Boiler's ultra low NOx, 119 hp (4,106 lbs/hr) Superior skid-mounted boiler system is designed at 200 psig pressure, firing natural gas. It is fully piped and wired and includes the following components:

- 119 hp Superior Apache Package Firetube Boiler
- Webster JBEX Ultra Low NOx Burner
- 2" Maxitrol 210D Gas Pressure Regulator (mounted)
- NEMA 4 Control Panel w/ Siemens LMV Parallel Positioning Controls
- Valve Trim (safeties, drain, etc.)
- Blowdown Valves (mounted & pre-piped)
- Duplex Feedwater System w/ Condensate Return Tank & Preheater (mounted & pre-piped)
- ASME Blowdown Separator with Aftercooler Package (mounted & pre-piped)
- Non-return Valve & 2nd Steam Gate Valve (loose)
- Single Point 480V Electrical Disconnect Connection w/ Step Down 115V Transformer
- 4" x 2 1/2" ASME Reducer Spool (loose)
- Stub Stack (loose)
- Meets ASME Section I, Cal Code & CSD-1 Requirements
- Weatherproofed (except for freezing conditions)
- Operating Manuals on CD's

Factory Integrated Skid Design Reduces Installation Time & Costs!



Fuel Consumption:

Natural Gas: 4,998 SCFH @ 2-10 psig

Connection Sizes:

2 1/2" -300# FLG Steam:

Natural Gas: 2" NPT Blowdown / Drain: 1 1/4" NPT Condensate Return: 2" NPT Make-up Water: 3/4" NPT Feedwater: 1 1/4" NPT Stack: 18"

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 35 AMPS

Dimensions & Weights:

Length: 16' 3" Width: 8' 4" 8'8" Height: Shipping Weight: 15,000 lbs Operating Weight: 23.000 lbs

Emissions Data (natural gas):

NOx (corr. to $3\% O_2$): 7 ppm CO (corr. to $3\% O_2$): 50 ppm

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.