

# Rentals • Sales • Service 24/7 • (800) 227-1966

## 47.5 HP - New In Stock Ultra Low NOx, 150 psig Skid-Mounted Boiler System

Nationwide Boiler's ultra low NOx, 47.5 hp (1,640 lbs/hr) Superior skid-mounted boiler system is designed at 150 psig pressure, firing natural gas. It is fully piped and wired and includes the following components:

- 47.5 hp Superior Apache Package Firetube Boiler
- PowerFlame NP2 Ultra Low NOx Burner
- 2" Maxitrol 210D Gas Pressure Regulator (mounted)
- NEMA 4 Control Panel w/ Siemens LMV Parallel Positioning Controls
- Valve Trim (safeties, drain, etc.)
- Blowdown Valves (mounted & pre-piped)
- Duplex Feedwater System w/ Condensate Return Tank & Preheater (mounted & pre-piped)
- ASME Blowdown Separator with Aftercooler Package (mounted & pre-piped)
- Non-return Valve & 2nd Steam Gate Valve (loose)
- Single Point 480V Electrical Disconnect Connection w/ Step Down 115V Transformer
- 4" x 21/2" ASME Reducer Spool (loose)
- Stub Stack (loose)
- Meets ASME Section I, Cal Code & CSD-1 Requirements
- Pre-certified for use in the South Coast AQMD and San Joaquin Valley APCD
- Weatherproofed (except freezing conditions)
- · Operating Manuals on CD's

Factory Integrated Skid Design Reduces
Installation Time & Costs!



Fuel Consumption:

Natural Gas: 1,998 SCFH @ 2-10 psig

Connection Sizes:

Steam: 2 ½"-300# FLG

Natural Gas: 2" NPT
Blowdown / Drain: 4"-300# FLG
Condensate Return: 2" NPT
Make-up Water: ½" NPT
Feedwater: ½" NPT
Stack: 8"

#### **Electrical Power Service Requirements:**

480 VAC, 3 ph, 60 hz, 25 AMPS

### Dimensions & Weights:

 Length:
 12" 6"

 Width:
 7' 2"

 Height:
 7' 6"

 Shipping Weight:
 8,600 lbs

 Operating Weight:
 12,000 lbs

#### Emissions Data (natural gas):

NOx (corr. to  $3\% O_2$ ): 9 ppm CO (corr. to  $3\% O_2$ ): 50 ppm

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com

True Nationwide Coverage & Beyond. Representatives Located Worldwide.