

# Rentals • Sales • Service 24/7 • (800) 227-1966

# 119 HP Ultra Low NOx, 200 psig Skid-Mounted Boiler System

Nationwide Boiler's ultra low NOx, 119 hp (4,106 lbs/hr) Superior skid-mounted boiler system is designed at 200 psig pressure, firing natural gas. It is fully piped and wired and includes the following components:

- 119 hp Superior Apache Package Firetube Boiler
- PowerFlame NP2 Ultra Low NOx Burner
- 2" Maxitrol 210D Gas Pressure Regulator (mounted)
- NEMA 4 Control Panel w/ Siemens LMV Parallel Positioning Controls
- Valve Trim (safeties, drain, etc.)
- Blowdown Valves (mounted & pre-piped)
- Duplex Feedwater System w/ Condensate Return
   Tank & Preheater (mounted & pre-piped)
- ASME Blowdown Separator with Aftercooler Package (mounted & pre-piped)
- Non-return Valve & 2nd Steam Gate Valve (loose)
- Single Point 480V Electrical Disconnect Connection
   w/ Step Down 115V Transformer
- 6" x 2 1/2" ASME Reducer Spool (loose)
- Stub Stack (loose)
- Meets ASME Section I, Cal Code & CSD-1 Requirements
- Weatherproofed (except for freezing conditions)
- Operating Manuals on CD's

Factory Integrated Skid Design Reduces
Installation Time & Costs!



#### **Fuel Consumption:**

Natural Gas: 4,998 SCFH @ 2-10 psig

#### Connection Sizes:

Steam: 2 ½"-300# FLG
Natural Gas: 2" NPT
Blowdown / Drain: 4"-300# NPT
Condensate Return: 2 ½" NPT
Make-up Water: ¾" NPT
Feedwater: 1 ¼" NPT
Stack: 16.5"

### **Electrical Power Service Requirements:**

480 VAC, 3 ph, 60 hz, 35 AMPS

# Dimensions & Weights:

 Length:
 16' 3"

 Width:
 8' 4"

 Height:
 8' 8"

 Shipping Weight:
 14,000 lbs

 Operating Weight:
 22,000 lbs

## Emissions Data (natural gas):

NOx (corr. to 3% O<sub>2</sub>): 9 ppm CO (corr. to 3% O<sub>2</sub>): 50 ppm

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com

True Nationwide Coverage & Beyond. Representatives Located Worldwide.