

Rentals • Sales • Service 24/7 • (800) 227-1966

200,000 pph, 750 psig 750°F Superheat, Low NOx Skid-Mounted Boiler

Nationwide Boiler's low NOx 200,000 pph, 750 psig design (400-675 psig operating), superheat steam, skid-mounted package watertube Babcock & Wilcox boiler is set to burn natural gas, hydrogen-blended fuels or #2-6 oil. It is piped and wired and includes the following components:

- Low NOx Burner
- EconoStak Economizer
- Allen-Bradley PLC Based Burner Management System with Fully Metered Combustion Controls
- Forced Draft Fan & Motor (no starter)
- Complete Fuel Train & Pilot Ignition System
- Water Column & Site Glass
- Steam Pressure Gauge
- Low-water Cutoffs
- Safety Valves
- Feedwater Stop & Check Valves
- Blowdown Valves
- Continuous Blowdown Metering Valve
- Chemical Feed Valve
- Flues & Ducts
- Main Steam Non-return Valve
- Stack
- NEMA 4 Electrical Enclosure
- Low NOx CataStak[™] SCR System (optional)
- Weatherproofed (except for freezing)
- Meets FM, NFPA 85 & IRI Insurance Standards
- Electronic Operating Manuals



Fuel Consumption: Natural Gas: #2 Oil:

Connection Sizes:

Main Steam: Natural Gas: #2 Oil Supply / Return: Feedwater: Bottom Blowdown: Continuous Blowdown: Chemical Feed: Atomizing Air: Atomizing Steam: Instrument Air: Water Column Drain: 286,000 SCFH @ 20 psi reg. 1974 GPH

10"-600# FLG 6"-150# FLG 1½" NPT / 1½" NPT 4"-600# FLG 1½"-600# FLG 1" NPT ½" NPT 1" NPT 1200 pph @ 80 psig 1" NPT 1200 pph @ 656 psig ½" NPT ¾" NPT

Electrical Power Service Requirements:

4160 / 2300 VAC, 3 ph, 60 hz, 600 HP Standard* • Optional Voltage 50Hz Available

Boiler Dimensions & Weights:

Length / Width / Height:	46' 6" / 12' 6" / 17' 4"
Shipping Weight:	216,000 lbs
Operating Weight:	274,000 lbs

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.

Ultra Low NOx Solutions