



Rentals • Sales • Service
24/7 • (800) 227-1966

350 HP Superior Low NOx, 250 psig Skid-Mounted Boiler

Nationwide Boiler's low NOx, 350 hp (12,075 lbs/hr) Superior Model 7-X-1500-S250-WBCF-G skid-mounted boiler, designed at 250 psig pressure, firing natural gas. It is fully piped and wired and includes the following components:

- 350 hp Mohican Firetube Boiler
- Webster Low NOx Burner
- Complete Gas Train
- NEMA 12 Control Panel w/ Siemens LMV Parallel Positioning Controls (indoor rated)
- Valve Trim (safeties, blowdown, etc.)
- Steam Pressure Gauge
- Low Water Cutoffs (primary & auxiliary)
- Water Column & Site Glass
- Modulating Feedwater Control Valve
- High/Low Water & Flame Failure Alarms
- Meets UL / CSD-1 / NFPA 85
- Electronic Operating Manual



Fuel Consumption:

Natural Gas: 14,700 SCFH @ 5 psig

Connection Sizes:

Main Steam: 6"-300# FLG
 Natural Gas: 3" NPT
 Blowdown / Drain: 1½ " NPT
 Feedwater: 2" NPT
 Chemical Feed: 1" NPT

Electrical Power Service Requirements:

460 VAC, 3 ph, 60 hz, 22 AMPS

Dimensions & Weights:

Length: 20' 2"
 Width: 8' 4"
 Height: 8' 10"
 Shipping Weight: 31,200 lbs
 Operating Weight: 49,400 lbs

Emissions Data (natural gas):

NOx (corr. to 3% O₂): 30 ppm
 CO (corr. to 3% O₂): 50 ppm

Ask About Our **Green Solutions**



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com
 True Nationwide Coverage & Beyond. Representatives Located Worldwide.

* Actual equipment may differ from listed specification. Please consult Nationwide Boiler Inc. for additional details.