

47.5 HP - In Stock **Ultra Low NOx, 150 psig Vertical Boiler System**

Nationwide Boiler's ultra low NOx, 47.5 hp (1,640 lbs/hr) Hurst vertical boiler system is designed at 150 psig pressure, firing natural gas. It is fully piped and wired and includes the following components:

- 47.5 hp Hurst 4-Pass Vertical Boiler
- Powerflame NPM-50 Burner
- Two (2) Low Water Cutoffs
- NEMA 4 Control Panel w/ Siemens LMV Linkageless Controls
- Manual Reset High Limit Pressure Control
- Blowdown Valves (Mounted & Pre-Piped)
- Operating Steam Pressure Limit
- Steam Pressure Transmitter w/ LMV3
- SS Chemical Injection Quill
- Valve Trim (Feedwater, Blowdown, and Steam; Factory Mounted)
- Two (2) Safety Relief Valves (Shipped Loose)
- Stack Thermometer (Shipped Loose)
- **NBI Propriety External Jacketing**
- Set of Seismic Anchor Clips and Center of Gravity Drawings
- Meets IRI, Factory Mutual, and Cal Codes
- CSD-1 and UL approved
- Pre-certified for SCAQMD Rule 1146.2
- **Electronic Operating Manual**

Factory Integrated Skid Design Reduces Installation Time & Costs!



Fuel Consumption:

Natural Gas: 1,950 SCFH @ 1 psig

Connection Sizes:

Steam Outlet: 2.5"-150# FLG

Natural Gas: 1/2" NPT Blowdown: 11/4 " NPT Feedwater: 1" NPT Stack: 12" OD

Electrical Power Service Requirements:

460 VAC, 3 ph, 60 hz, 20 AMPS

Dimensions & Weights:

Length: 9' 5" Width: 5' 2" Height: 8' 7" Shipping Weight: 5,500 lbs Operating Weight: 6,700 lbs

Emissions Data (natural gas):

NOx (corr. to $3\% O_2$): 20 ppm CO (corr. to 3% O₂): 50 ppm

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.