

500 hp Low NOx, 250 psig **Trailer Enclosed Boiler**

Nationwide Boiler's low NOx, 500 hp (17,250 lbs/hr) trailer enclosed Cleaver-Brooks firetube boiler is designed at 250 psig pressure, firing natural gas or #2 oil. It is fully piped and wired and includes the following components:

- Low NOx Burner with Induced Flue Gas Recirculation (IFGR) for 30 PPM NOx
- Forced Draft Fan, 30 hp Motor & Starter •
- Complete Gas Train
- Oil System with Pump & Air Compressor (loose) •
- Steam Pressure Gauge .
- Dual Low Water Cutoffs .
- Water Column & Site Glass •
- Two (2) Safety Relief Valves Set at 250 psig
- Feedwater Stop and Check Valves .
- Bottom & Control Blowdown Valves •
- Continuous Blowdown Metering Valve .
- Control Panel w/ Combustion Safeguard Control •
- High/low Water and Flame Failure Alarm
- . Pilot System w/ Electric Ignition
- . Main Steam Non-return Valve (loose)
- Stack (loose) •
- NEMA 3 Disconnect (unfused/mounted) •
- Meets FM / IRI / NFPA 85 .
- EconoStak Economizer (optional) .
- Low NOx CataStak[™] SCR System (optional) .
- Service and Operating Manuals
- Boiler Includes All Canada CRN and Seismic Zone 3 & 4 Design



Fuel Consumption: Natural Gas: #2 Oil:

19,900 SCFH @ 5 psig 142 GPH

Connection Sizes:

Main Steam: Natural Gas: #2 Oil Supply / Return: Feedwater: Blowdown Drain: Make-up Water:

8"-300# FLG 3"-150# FLG 1" NPT / 1" NPT 2"-300# FLG 6"-300# FLG 2"-150# FLG

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 150 AMPS

Boiler Dimensions & Weights:

40' 6"
8' 0"
13' 6"
58,680 lbs
70,530 lbs

Emissions Data (natural gas):

NOx (corr. to 3% O ₂):	30 ppm
CO (corr. to 3% O ₂):	50 ppm

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.