

## **Rentals • Sales • Service**

## 90,000 pph, 395 psig **Indeck D-Type Package Watertube Boiler**

One (1) 90,000 PPH 395 psig saturated steam, package watertube boiler is set to burn natural gas (#2 oil is optional). It was originally built in 2012 and includes the following components:

- Low NOx Burner
- **Economizer**
- Burner Management System
- Parallel Positioning Combustion Controls
- Forced Draft Fan, Motor & Starter
- Complete Fuel Train & Pilot Ignition System
- Water Column & Site Glass
- Steam Pressure Gauge
- Low-water Cutoffs
- Safety Valves
- Feedwater Stop & Check Valves
- Blowdown Valves
- Continuous Blowdown Metering Valve
- Chemical Feed Valve
- Single Element Feedwater Regulator with Pre-piped 3-Valve Bypass
- Steam Non-return Valve
- FGR Ductwork (loose)
- Stack (loose)
- **NEMA 4 Electrical Enclosures**
- Separate Fuel Oil Skid for #2 Oil Firing (optional)
- Ultra Low NOx CataStak™ SCR System (optional)
- Weatherproofed (except for freezing)
- ASME, FM, NFPA 85 & GE Gap Insurance Compliant
- **Electronic Operating Manuals**



Fuel Consumption:

Natural Gas: 109,900 SCFH @ 15-25 psi reg.

#2 oil (optional) 700 GPH

Connection Sizes:

Main Steam: 8"-300# FLG Natural Gas: 4"-150# FLG

#2 oil supply/return 11/4 "-150# FLG / 3/4"-150# FLG

Feedwater: 3"-300# FLG Bottom Blowdown: 1½"-300# FLG

Continuous Blowdown: 1" NPT Chemical Feed 1" NPT Atomizing Steam: 1"-150# FLG Instrument Air: 1/2" NPT Water Column Drain: 3/4" NPT

## **Electrical Power Service Requirements:**

480 VAC, 3 ph, 60 hz, 250 AMPS

Dimensions & Weights:

32' 7" / 11' 5" / 14' 6" Length / Width / Height:

Shipping Weight: 105,000 lbs Operating Weight: 136,500 lbs

Emissions Data (natural gas):

NOx (corr. to  $3\% O_2$ ): 30 ppm CO (corr. to 3% O<sub>2</sub>): 50 ppm

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.